



The **KVM 1708** is a professional 8-port KVM-Switch with integrated an extendable keyboard and a 17" TFT LCD monitor. This device is mainly used to centralise the operation of numerous servers in server cabinets via the integrated KVM-switch.

The integrated password protection avoids the access to the keyboard and monitor and protect your server again unauthorised users.

The KVM can be connected alternatively by PS/2 or USB via 8 provided connection cables.

## **Specifications**

Keyboard	104-Key with Touchpad (QWERTY-Keyboard)
Monitor	17" TFT LCD
Output	8
Max. number of administrable PCs	256
For Cabinet	800-1000mm
Connectors	D-SUB15 (LCD, PS2/USB Keyboard, Mouse) OSD Switch
Support OS	Non Restrictions
Switch Modi	Hotkey OSD Menu
Switch Scan Time	1-255s (OSD adjustable)
DDC	•
Display Resolution	1280x1024
Display Frequency Range	75Hz
Display Brightness	300lm
Display Contrast	1000:1
Power Supply	External Power Supply
Input	AC100-240V 47-63HZ 30W
Material	Anti-corrosion steel plate
Operating Temperature	-10°C~60°C
Storage Temperature	-30°C~70°C
Humidity	0-80%
MBTF	Average 120000h
Net Dimensions (H/W/D)	44x440x570mm
Gross Dimensions (H/W/D)	200x620x710mm
Weight (net)	13.99 Kg
Weight (gross)	21.39 Kg
Packing Units	Shipping Unit: 1 Piece Pallet: 15 Pieces
Guarantee and Warranty	24 Months Guarantee
Article Number	88887058
EAN-Code	4260133122925
Scope of Delivery	8x KVM Cable VGA / PS/2 / USB (180cm) Installation rail set Keys Power Supply Power Cord Manual (german) Warranty Card
Features	8x Hotkeys Panel lockable
Optional Accessory	Password protection for keyboard and monitor KVM Cable VGA / PS/2 / USB (300cm) (Art. 88887055) KVM Cable VGA / PS/2 / USB (500cm) (Art. 88887056) KVM Cable VGA / PS/2 / USB (1000cm) (Art. 88887057)

• = existing  
- = non existing