

Thunder



Thunder – let it crack!

For those who like design, the Thunder with its slightly tinted side panel made of Plexiglas and the switchable LED light on the front is the ideal candidate for a PC system with trendy LED lighting and a 120mm fan with blue LED lighting at the back as standard. Two additional installation options for 120mm fans in the front also improve the airflow in the case.

On the top of the case are USB 2.0 and 3.0 ports, the HD audio jacks and the LED button, with which the LED lighting in the front panel can be manually switched on and off. A removable dust filter under the power supply and a variety of ways to lay the cables, complete the offer.

- √ trendy LED lighting in the front panel
- ✓ modern design
- ✓ blue illuminated 120mm LED fan as standard
- √ Side panel made of Plexiglas



Thunder

Specifications

Motherboard ATX, µATX, ITX 5.25" external: 0 Max. drive bays 3.5" external: 0 3.5" internal: 2 2.5" internal: 2 Front connectors USB 3.0: 1 USB 2.0: 2 Microphone: 1 Speaker: 1 Cooling system Front: 2x 120mm (optional) Rear: 1x 120mm (serial, blue LEDs, 3pin and Molex connector) Max CPU-Cooler height 160mm Max Graphic card length 330mm Packing units Shipping unit: 1 pcs Packing unit: 28 pcs Warranty 24 Months Article number 88881309 EAN-Code 4260455643634 Scope of Delivery Screw set Speaker **Features** Front panel with blue LED strip Tinted window side panel 1x 120mm fan with blue LEDs on the back as standard LED button to switch the LED strip in the front panel on and off Two 3.5" bays below the motherboard carrier with separate airflow Place for water cooling in sizes of 120mm and 240mm Power supply mounting in a separate cage in the bottom part Openings for easy laying of cables Easy-to-remove dust filter below the power supply Stands

Dimensions and Weight

	Cage	Case	Package
Height	410mm	425mm	460mm
Width	180mm	195mm	220mm
Depth	370mm	410mm	465mm
Weight (ne Weight (gr	et): 3.06kg oss): 3.82k	κg	

ower Supply	Ĺ	
Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	4
P8 12V 8Pin	_ · _	417
PCI-Express 6+2Pin		
PCI-Express n	tho	
IDE 4Pin		-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Certification: