

	SW-0816 Art.-No. 88887284	SW-1681 Art.-No. 88887235	SW-1081 Art.-No. 88887029	SD-1688 Art.-No. 88887381	M-1681 Art.-No. 88887073	ST-1021 Art.-No. 88887075	SD-1021 Art.-No. 88887386
Technical data	Input voltage	AC 230V~	AC 230V~	AC 230V~	AC 230V~	AC 230V~	AC 230V~
	Total current	16A	16A	10A	16A	16A	10A
	Current per outlet	10A	10A	10A	16A	10A	10A
	Input socket	1x C20	1x C20	1x C20	1x C20	1x C20	1x C14
	Output socket	8x C13	8x C13	8x C13	8x C13	8x C13	2x C13
	Network socket	1x RJ45	1x RJ45	1x RJ45	1x RJ45	1x RJ45	1x RJ45
	Transfer rate	10 Mbit/s	10 Mbit/s	10 Mbit/s	100 Mbit/s	10 Mbit/s	100 Mbit/s
	Network protocol	IPv4	IPv4	IPv4	IPv4 / IPv6	IPv4	IPv4 / IPv6
	Bus socket	-	-	-	2x RJ11	1x RJ11	1x RJ11
	Fuse	+	+	+	+	+	-
	Display	+	+	+	+	+	-
	LED display	front	front	front	front	front	front and rear
	Firmware Update	-	-	-	+	-	+
	Config. save/ recover	-	-	-	+	-	+
Handling	Cable	C19 to C20	C19 to C20	C19 to C14	C19 to C20	fixed	C14 to C13
	Cable length	2 m	3 m	2 m	2 m	2 m	2 m

Handling	At the device	-	-	-	-	-	-	-
	By Web interface	+	+	+	+	Only usable with control unit C-81	+	+
	By Software	+	+	+	+	Only usable with control unit C-81	+	+

Monitoring	Total current (A)	+	+	+	+	+	+	+
	Current per outlet (A)	-	-	-	+	-	-	-
	Temperature/ Humidity	+	-	-	only with optional sensor	only with optional sensor and control unit C-81	-	only with optional sensor

Switching	Outlet switching	+	+	+	+	-	+	+
	Group switching	-	+	+	+	-	+	+
	Autom. Off/On switching	+	+	+	+	-	+	+
	Scheduled switching	-	-	-	+	-	+	+
	Ping action	-	-	-	+	-	+	+

Adjustable thresholds	Total current	+	+	+	+	Only usable with control unit C-81	+	+
	Voltage	+	+	+	+	Only usable with control unit C-81	+	+
	Current per outlet	-	-	-	+	-	-	-
	Temperature/ Humidity	+	-	-	-	only with optional sensor	only with optional sensor	only with optional sensor

	SW-0816 Art.-No. 88887284	SW-1681 Art.-No. 88887235	SW-1081 Art.-No. 88887029	SD-1688 Art.-No. 88887381	M-1681 Art.-No. 88887073	ST-1021 Art.-No. 88887075	SD-1021 Art.-No. 88887386
Alarm	Exceeding total current threshold	+	+	+	+	Only usable with control unit C-81	+
	Exceeding single current threshold	-	-	-	+	-	-
	Exceeding temperature/ humidity threshold	+	-	-	only with optional sensor	only with optional sensor and control unit C-81	only with optional sensor
Alarm notification	By LED	+	+	+	+	+	+
	Acoustic	+	+	+	+	+	-
	By Web interface	+	+	+	+	+	+
	Email	Only with software	+	+	+	Only usable with control unit C-81	+
User	Multiple users	-	-	-	+	-	-
	Radius user administration	-	-	-	+	-	+
Network	DHCP	+	+	+	+	Only usable with control unit C-81	+
	Manual IP address	+	+	+	+	Only usable with control unit C-81	+
	SNMP	-	+	+	+	Only usable with control unit C-81	+
	HTTPS	-	-	-	+	-	-
	IP Filter	-	-	-	+	-	+
Dimension	Height	1 HU	1 HU	1 HU	1 HU	1 HU	4 cm
	Width	19"	19"	19"	19"	19"	12 cm
	Depth	13,5 cm	8,9 cm	8,9 cm	22,8 cm	6,5 cm	10 cm
							5,8 cm
							12 cm
							8,8 cm

