Inter-Tech Elektronik Handels GmbH

IPC 4U-40248

The IPC **4U-40248** is the perfect rack for a cost-effective server system. Due to the excellent material quality combined with the excellent workmanship, Inter-Tech has created the basis for an extremely variable case.

So offers the **IPC 4U-40248** the option of removing the mounting frame on both sides and thus installing up to six additional 5.25" external drives, up to 3x 5.25" external drives are available as standard. A maximum of 11x 3.5" or 4x 2.5" hard drives can be installed internally, depending on the configuration.

In addition, two 120mm and two 80mm fans reliably ensure optimal cooling.

Two easily accessible USB 3.0 front ports in the front and the lid with two snap-in closures complete the package.

Inter-Tech Elektronik Handels GmbH

Specifications

Motherboard	Mini-ITX, mATX, µATX, ATX, SSI CEB
	maximal motherboard size BxT: 305mm x 267mm, 12" x 10.5"
Drive bays	5.25" external: 3*
	3.5" internal: 11*
	2.5" internal: 4*
Front connectors	USB 3.0: 2
Cooling system	Front: 2x 120mm
	(included, Molex connector)
	6x 40mm
	(optional, behind the 5.25"brackets)
	Rear: 2x 80mm
	(included, 3pin connector)
Controls	Power-Button
	Reset-Button
LED	Power
	HDD Activity
	3x Network Activity
	Alert
Power supply	ATX-/Redundant-PSU
Material	1.0-1.2mm Steel
Maximum CPU cooler height	150mm
Maximum graphics card length	267mm
Packing units	Shipping unit: 1 piece
	Pallet: 15 pieces
Warranty	24 Months
Article number	88887303
EAN-Code	4260455645928
Scope of delivery	Screw Set
	Mounting rails for 3.5" hard drives
	Mounting frame for redundant power supplies
Features	7 slot openings
	2x 120mm and 2x 80mm fan included
	Up to 6x 40mm fan optional mountable
	Lid with snap lock

*can vary by using several mounting options

Dimensions and Weight

	Cage	Case	Package
Height	177.8mm	177.8mm	250mm
Width	433mm	485mm	560mm
Depth	480mm	525mm	675mm

Weight (net): 10.69kg
Weight (gross): 12.82kg

Power Supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	
P8 12V 8Pin	-	
PCI-Express 6+2Pin	-	
PCI-Express 6Pin		-
IDE 4Pin		-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Without

Certification: CE