



## IPC

The **IPC 4U-4508** is the ideal case for a small and cheap server solution. With its excellent quality and finish, Inter-Tech established the base for a very variable case.

It offers the possibility to install eight 2.5" or 3.5" Hot-Swap HDDs, two 5.25" external drives or two internal 2.5" HDDs.

The **4U-4508** has two 80mm included and space for two more optional 80mm fans to ensure reliable and optimal cooling.

Two USB 3.0 connectors in the front complete the offer.

## Specifications

Mainboard	Mini ITX, mATX, ATX, E-ATX, SSI EEB* Max. Mainboard size WxD: 305mm x 345mm, 12" x 13,5"
Max. Drive Bays	2.5" or 3.5" external Hot-Swap (max. 6G): 8 5.25" external: 2 2.5" internal: 2
Front Connectors	USB 3.0: 2
Cooling System	Front: 2x 80mm (Molex) Rear: 2x 80mm (optional)
Controls	Power-Button Reset-Button
LED	Power HDD Activity
Power Supply	ATX / Redundant PSU
Material	1.0-1.2mm Steel
Maximum CPU cooler height	115mm
Maximum graphics card length	250mm
Packing Units	Shipping Unit: 1 piece Pallet: 9 pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	8887336
EAN-Code	4260455646437
Scope of Delivery	Screw set Mounting bracket for ATX and 4U redundant PS/2 (pre-assembled)
Features	2x 80mm fan included Drive brackets removable USB 3.0 and USB 2.0 as block connector Hot-Swap backplane with SATA socket Lockable Hot-Swap frame

Front side of the E-ATX and SSI motherboards may not have any components higher than 3cm on a length of 4cm.

## Dimensions and Weight

	Cage	Case	Package
Height	178mm	178mm	290mm
Width	430mm	480mm	575mm
Depth	480mm	530mm	655mm

Weight (net): 11.185kg  
Weight (gross): 14.33kg

## Power Supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

**Without**

Certification:

