



IPC 2U-2404S

The **IPC 2U-2404S** is the perfect rack for a low-priced storage system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

The **IPC 2U-2404S** offers the possibility to mount maximal four 2.5" or 3.5" Hot-Swap HDDs and one internal 2.5" or 3.5" HDD (by using a 2.5" with 9.5mm height also a 3.5" HDD simultaneously). The **IPC 2U-2404S** is equipped with three serial 40mm fans. At the rear of the chassis you can mount an ATX PSU with 80mm fan.

Specifications

| | |
|------------------------------|---|
| Motherboard | Mini-ITX, µATX max. motherboard size WxD: 244mm x 244mm, 9.6" x 9.6" |
| Drive Bays | 2.5" or 3.5" Hot-Swap (max. 12G): 4 2.5" or 3.5" internal: 1 ¹ |
| Front Connectors | USB 3.0: 1 USB 2.0: 1 |
| Cooling System | Internal: 3x 40mm (serial, 3Pin with 4Pin connector) |
| Controls | Power-Button Reset-Button |
| LED | Power HDD Activity 3x Network Activity 1x Alert |
| Power Supply | ATX PSU with 80mm fan |
| Material | 1.0-1.2mm steel |
| Maximum CPU cooler height | 32mm/65mm* |
| Maximum graphics card length | 190mm |
| Packing Units | Shipping Unit: 1 Piece Pallet: 21 Pieces |
| Guarantee and Warranty | Case 24 Months Warranty |
| Article Number | 88887190 |
| EAN-Code | 4260133128613 |
| Scope of Delivery | Screw Set Mounting frame for ATX PSU Mounting tool |
| Features | Serial 3x 40mm fans 4x perforated Low-Profile slot bracket (Rear) USB 3.0 and USB 2.0 internal as block connector Hot-Swap backplane with SFF 8087 socket (max. 12 G) ² Mesh-Grid-Front |

¹simultaneously only if 2.5" drive with max. 9.5 mm height

² The backplane is only compatible with a SAS-Controller with SFF-8087 connector.

To use the backplane with a SATA-Controller, please order the optional SFF8087 cross-over cables (88885237) in right quantity
*depending on the position of the CPU (32mm, if the CPU is under the HDD cage)

Dimensions and Weight

| | Cage | Case | Package |
|-----------------|--------|-------|---------|
| Height | 89mm | 89mm | 155mm |
| Width | 433mm | 482mm | 550mm |
| Depth | 400mm | 438mm | 560mm |
| Weight (net): | 5.97kg | | |
| Weight (gross): | 7.67kg | | |

Power Supply

| Connector | Quantity | Max. Length |
|--------------------|----------|-------------|
| Mainboard 20+4Pin | - | - |
| P4 12V 4Pin | - | - |
| P4/EPS 4+4Pin | - | - |
| P8 12V 8Pin | - | - |
| PCI-Express 6+2Pin | - | - |
| PCI-Express 6Pin | - | - |
| IDE 4Pin | - | - |
| S-ATA | - | - |
| Floppy | - | - |
| RPM sensor cable | - | - |
| Fan Control | - | - |
| Fan: 120mm | - | - |

Without

Certification:

