



IPC 1U-1404

The **IPC 1U-1404** is the ideal case for a small and cheap server solution. With its excellent quality and finish, Inter-Tech established the basis for a very variable case.

The **IPC 1U-1404** offers the possibility to install maximal four 2.5" or 3.5" Hot-Swap HDDs, one Slim DVD external and three internal 2.5" HDDs. The **IPC 1U-1404** has five 40mm fans included, which are mounted directly at the back of the drive brackets and ensure therefore a reliable and optimal cooling.

Additional extras like the reusable and perforated slot bracket, the universal ATX I/O plate and the lid with the snap lock round off the picture.

Specifications

| | |
|------------------------------|--|
| Motherboard | Mini ITX, µATX, ATX, eATX, SSI EEB maximal motherboard size WxD: 305mm x 345mm, 12" x 13.5" |
| Drive Bays | 4x 2.5" or 3.5" Hot-Swap (max. 6G) 1x drive bay Slim DVD for 1x Slim DVD or 1x 2.5" internal hard drive 2x drive bays 2.5" for 1x 2.5" internal hard drive |
| Front connectors | USB 2.0: 2 |
| Cooling System | Internal: 10x 40mm (5x included, Molex connector and 5x optional) |
| Controls | Power-Button Reset-Button |
| LED | Power HDD Activity 3x Network Activity Alert |
| Power Supply | 1U Server Power Supply |
| Material | 1.0-1.2mm Steel |
| Maximum CPU cooler height | 32mm |
| Maximum graphics card length | 345mm |
| Packing Unit | Shipping Unit: 1 piece Pallet: 27 pieces |
| Guarantee and Warranty | Case 24 Months Warranty |
| Article Number | 88887115 |
| EAN-Code | 4260133126367 |
| Scope of Delivery | Screw Set Assembly tool Mounting brackets for 1HU PSU |
| Features | 5x 40mm fan included Drive brackets removable Reusable and perforated slot bracket (rear with optional riser card) Universal ATX I/O plate (rear) Snap locks USB 2.0 as block connector Hot-Swap backplane with SFF-8087 connectors* |
| Optional Accessories | Lockable frontgrill 1HU silver (Article number: 88887114) |

*The included backplanes only support SAS-Controller with SFF-8087 connection.
In operation with SATA-Controllers, please order the optional available SFF8087 cross-over cables (Art.-No. 88885237) in right quantity.

Dimensions and Weight

| | Cage | Case | Package |
|--------|--------|--------|---------|
| Height | 44.5mm | 44.5mm | 110mm |
| Width | 433mm | 481mm | 560mm |
| Depth | 650mm | 678mm | 830mm |

Weight (net): 7.94kg
Weight (gross): 10.02kg

Power Supply

| Connector | Quantity | Max. Length |
|--------------------|----------|-------------|
| Mainboard 20+4Pin | - | - |
| P4 12V 4Pin | - | - |
| P4/EPS 4+4Pin | - | - |
| P8 12V 8Pin | - | - |
| PCI-Express 6+2Pin | - | - |
| PCI-Express 6Pin | - | - |
| IDE 4Pin | - | - |
| S-ATA | - | - |
| Floppy | - | - |
| RPM sensor cable | - | - |
| Fan Control | - | - |
| Fan: 120mm | - | - |

Certification:

