



IPC 1.5U-1528L

The **1.5U-1528L** is the perfect rack for a small server system. The special design in 1.5U enables you to run two external drives (2.5" or 3.5") in Hot-Swap mode on an ITX-Mainboard base. The interior offers the option to mount two additional 2.5" drives and more height for CPU-cooler than a regular 1U case.

Two serial 60mm fans behind the front panel ensure a reliable cooling. It also offers two USB front connectors in the front, next to the controls.

- ✓ more space than 1U racks
- ✓ 2x 60mm Fan
- ✓ Depth only 280mm
- ✓ Aluminum front

Specifications

Motherboard	Mini-ITX
Drive Bays	Max board dimensions WxH: 170mm x 170mm, 6.7" x 6.7" 2.5" or 3.5" Hot-Swap (max. 6G): 2 2.5" internal: 2
Front Connectors	USB 2.0: 2
Cooling System	Front: 2x 60mm (serial, Molex connector)
Controls	Power-Button Reset-Button
LED	Power HDD Activity
Material	1.0-1.2mm Steel
Maximum CPU cooler height	40mm
Maximum graphics card length	170mm
Packing Units	Shipping unit: 1 Piece Pallet: 32 Pieces
Warranty	24 Months
Article Number	88887210
EAN-Code	4260455641722
Scope of Delivery	Screw Set
Features	Option to mount Flex-ATX PSU 's Only 280mm Depth (without grips) 2x 60mm serial fans Two Riser-Slots for expansion cards (full height max. 7cm depth, half height max. 9cm depth) USB 2.0 intern as block connector

Dimensions and Weight

	Cage	Case	Package
Height	65mm	65mm	185mm
Width	423mm	482mm	430mm
Depth	280mm	314mm	560mm

Weight (net): 4.29kg
Weight (gross): 6.03kg

Power Supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Certification:

