



## **IPC 1U-10265**

The **IPC 1U-10265** is the perfect rack for a low-priced server system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

The **IPC 1U-10265** provides the possibility to mount nine 2.5" and three 3.5" internal hard drives. Five standard 40mm fans guarantee an optimal cooling.

Additional extras like easily reachable USB 2.0 connectors and the universal ATX I/O plate complete this total package.

## Specifications

|                              |   |
|------------------------------|---|
| Motherboard                  | Mini ITX, mATX, $\mu$ ATX, ATX, eATX, SSI EEB<br>maximal motherboard size WxD: 305mm x 340mm, 12" x 13.3"   |
| Drive Bays                   | 5.25" Slim-DVD: 1*<br>5.25" external: 2*<br>3.5" internal: 3*<br>2.5" internal: 9*  |
| Front Connectors             | USB 2.0: 2  |
| Cooling System               | Internal: 10x 40mm<br>(5x included, Molex connector)  |
| Controls                     | Power-Button<br>Reset-Button  |
| LED                          | Power<br>HDD Activity<br>3x Network Activity<br>Alert   |
| Power Supply                 | 1U Server PSU, FLEX-ATX   |
| Material                     | 1.0-1.2mm Steel   |
| Maximum CPU cooler height    | 32mm  |
| Maximum graphics card length | 340mm   |
| Packing Units                | Shipping Unit: 1 Piece<br>Pallet: 27 Pieces   |
| Guarantee and Warranty       | Case 24 Months Warranty   |
| Article Number               | 88887102  |
| EAN-Code                     | 4260133126237   |
| Scope of Delivery            | Screw Set<br>Mounting frame 5.25" to Slim-DVD/3.5"  |
| Features                     | 5x 40mm fan included<br>USB 2.0 as block connector<br>Universal ATX I/O plate<br>1x Riser slot, screwless mounting, convertible for left and right mounting direction |

\*can vary by using several mounting options

## Dimensions and Weight

|        | Cage   | Case   | Package |
|--------|--------|--------|---------|
| Height | 44.5mm | 44.5mm | 110mm   |
| Width  | 433mm  | 482mm  | 555mm   |
| Depth  | 650mm  | 678mm  | 830mm   |

Weight (net): 7.80kg  
Weight (gross): 10.41kg

## Power supply

| Connector          | Quantity | Max. Length |
|--------------------|----------|-------------|
| Mainboard 20+4Pin  | -        | -           |
| P4 12V 4Pin        | -        | -           |
| P4/EPS 4+4Pin      | -        | -           |
| P8 12V 8Pin        | -        | -           |
| PCI-Express 6+2Pin | -        | -           |
| PCI-Express 6Pin   | -        | -           |
| IDE 4Pin           | -        | -           |
| S-ATA              | -        | -           |
| Floppy             | -        | -           |
| RPM sensor cable   | -        | -           |
| Fan control        | -        | -           |
| Fan 120mm          | -        | -           |

**Without**

Certification:

